



SUPER ERECTA SHELF® PRINTED CIRCUIT BOARD TRUCKS HORIZONTAL HOLD

- **Safe PCB Handling:** Metro PCB Trucks safely transport and store large circuit boards – or large quantities of small boards.
- **Two Sizes Available:** Trucks come in two lengths — 36" (910mm) and 48" (1220mm). Both models are 24" (610mm) wide.
- **High Density Storage:** Trucks provide 48 levels for circuit boards and offer $1\frac{1}{16}$ " (18mm) spacing for high density loading. Middle panel has extrusions on both sides. Slides accept boards up to $22\frac{1}{2}$ " (571mm) long and up to $\frac{1}{2}$ " (12.7mm) thick.
- **Adjustable:** Panels slide along side frames to the exact width of boards. Holding knobs at each panel corner are manually tightened to hold panels securely in place. To accommodate boards from 3" (75mm) to $22\frac{1}{2}$ " (570mm) deep, the vertical stop bar on the face of each panel can be placed in any location along the face of the panel.
- **Versatile:** Ideal for circuit board curing operations (if over 160°F [70°C], Hi Temp. Kit must be specified) as well as handling large quantities of unpopulated or populated boards.
- **Conductive:** All metal truck components eliminate electrostatic build-up in properly grounded units. Slides are natural finish extruded aluminum.
- **Super Erecta Shelf Construction:** Provides fast, secure assembly of unit without special tools.
- **Identifiable:** Numbering strip is standard for easy identification of storage levels.



SUPER ERECTA SHELF® PRINTED CIRCUIT BOARD TRUCKS HORIZONTAL HOLD



Specifications

- **Panels:** Natural finish extruded aluminum.
- **Frames:** Structural chrome-plated steel with tapered corner collars which attach to the posts via aluminum split sleeves and retaining rings, making it possible to position the panel/frame unit at the desired working level.
- **Load Rating:** 5 lbs. (2kg) per slide, 75 lbs. (34kg) per bay, 150 lbs. (68kg) maximum per unit.

Dimensions

Model No.	Width (in.) (mm)		Length (in.) (mm)		Height (in.) (mm)		Maximum Board Size without Center Panel (in.) (mm)		Capacity Full-Size Boards	Capacity 11" (275mm) Boards without Center Panel	Capacity 11" (275mm) Boards with 2 Center Panels	Approx. Pkd. Wt. (lbs.) (kg)	
CBL536BC	24	610	36	910	68	1727	22 ¹ / ₂ x 30 ¹ / ₄	571 x 768	48	96	192	105	48
CBL556BC	24	610	48	1220	68	1727	22 ¹ / ₂ x 42 ¹ / ₄	571 x 1073	48	96	192	120	54

Accessories

Center Panel Assembly (Offered as standard with each unit and as an accessory).

Model No.	Width (in.) (mm)		Length (in.) (mm)		Height (in.) (mm)		Approx. Pkd. Wt. (lbs.) (kg)	
CBLP2	23 ¹ / ₂	600	37 ¹ / ₄	945	1 ⁵ / ₈	41	24	11

Other Accessories

Model No.	Description	Approx. Pkd. Wt. (lbs.) (kg)	
HTK-I	High Temperature Kit (Includes 4 high temperature casters (two with brakes), two "Caution Hot" labels, and 4 metal post caps. Required for temperatures over 160°F [70°C]. Kit good to 400°F [205°C]).	13	6
IDK-IL	Label Identification Kit (contains two labels).		

